LED Adjustable Retrofit Trim

DIMENSIONS

APPLICATION

The LART Series LED down-light retrofit trim provides versatile lighting on standard line voltage, yet produces the high energy savings you desire from LED fixtures. The LART series allows for easy upgrade your down-lighting from the traditional recessed cans to a more modern looking, energy efficient solution. This down-light can be easily mounted onto a junction box or can be retrofitted into an existing recessed can with the optional hardware mounting adapter.

FEATURES

- High-transmission (White) Acrylic lens with excellent distribution and uniformity.
- Full distribution LED Luminaire.
- 100° Beam Angle
- Impact Resistant Acrylic Lens
- Can be retrofit into most 5" or 6" recessed down-lights or surface mounted for new construction applications.
- Designed for a 50,000 Hour Life
- Available in 2700K or 4000K Kelvin temperatures.
- Environmentally friendly - contains no mercury or other hazardous materials.
- IC rated when used in an approved IC rated recessed can.

HOUSING

Aluminium spun reflection with diffusion lens for official visual comfort while providing optional light output

MOUNTING

Can be retrofit into most 5" or 6" recessed down-lights or surface mounted for new construction applications.

ELECTRICAL

Equipped standard with 120V 15-100% triac dimming driver.

LISTING

All luminaires are built to UL 1598 and 2108 standards, and bear appropriate ETL labels. Damp location labeling is standard. Adheres to LM70, LM80, and TM21 industry standards.

WARRANTY

3-year limited warranty. See complete warranty for terms and exclusions. (Labor not included).

QUICK SHIP

Made to order only

ORDERING INFORMATION

Example Model Number: LART-4-10-120D-930-WH

SERIES	DIAMETER	WATTAGE	DRIVER TYPE	COLOR TEMPERATURE	FINISH
LART					
	4-4"[1] **6**- 6"[1]	4" Housing **10**-10W (780 Lumens)[1,2] 6" Housing **12**-12W (780 Lumens)[1,2] **17**-17W (1070 Lumens)[1,2]	**120D**- 120V, Triac Dimming[1,2]	**930**-90 CRI; 3000 Kelvin[1,2] **940**-90 CRI; 4000 Kelvin[1,2]	**WH**- White[1,2]

Notes:
[1]Made to order items. Minimum 90 day lead time. Minimum 500 order quantity.
[2]Energy star listed