



Project	
Notes	
Type	Date
Cat. No.	

REXS™ Series

Recessed Edge Lit LED Exit Sign

APPLICATIONS

The REXS Series is a recessed edge-lit LED exit sign that features an architectural, slim design to fit into an environment offering specification grade aesthetics with in field installation flexibility. Attractive and functional, the REXS series is completely self-contained and utilizes reliable, energy efficient LED illumination. REXS series edge-Lit exits are well suited for any application requiring attractive edge-lit exit signs. Typical installations include commercial spaces such as retail, offices or medical facilities but can be applied in any space where an upgrade appearance is desired.



REXS Series

- REXS-1-A-R
- REXS-1-A-G
- REXS-2-A-R
- REXS-2-A-G

Specification Features



Construction

Premium-grade, extruded aluminum housing. Extruded aluminum trim assembly is easily detachable from below, providing accessibility for service or maintenance. (Available in optional black or white powder-coated finishes). Self-adhesive Chevron appliques and guide template provided for directional indication.

Qualifications

Meets UL924, NFPA 11 life safety Code, NEC, OSHA Local and State Codes. UL listed for damp locations (0° C - 50° C).

Warranty

5-year Limited Warranty on all electronics and housing. Battery pro rated for 5 years.

Electrical

Dual 120/277 voltage. Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing. 4.8V long-life, maintenance - free, rechargeable NiCad battery. Internal solid-state transfer switch automatically connects the internal battery to the LED lamp head for minimum 90-minute emergency illumination. Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.

Installation

Compatible with drywall or drop ceiling mount installations. (Bar hangers included). Wall mount capability optional.

Limited Warranty 5-years

Quick Ship
Made to order only

Ordering Information

Example: REXS-1-A-R

REXS	2	W	R	AC	SD	
Series REXS Recessed Edge Lit LED Exit Sign	Faces 1 2	Housing W - White B- Black A- Aluminum	Lettering R - Red G - Green	Battery AC- AC Onlt	Option SD- Self Diagnostic 2C- Dual Circuit	

Specifications and Dimensions subject to change without notice.

Performance Summary

Input Voltage	120V/277V
Input Frequency	50/60 Hz
Rated Wattage	2.5W
Operating Temp.	0°C to 50°C
Rated Life	60,000 hours
L70	> 72,000 hours or > 45,000
Power Factor	> 0.9

Performance Data

Lens Type	Form Factor	Catalog No.	Rated Wattage (W)
None		REXS-1-W-R	2.5

NOTES:

- ¹ Made to order items. Minimum 90 day lead time. Minimum 500 order quantity.
- ² Quick ship: 3000K. Other CCTs may require a lead time or be special order.
- ³ Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C.



Specifications and Dimensions subject to change without notice.

Product Dimensions

REXS

