


**SAFETY INSTRUCTIONS**

**PLEASE READ THESE INSTRUCTIONS CAREFULLY AND SAVE THEM, AS YOU MAY NEED THEM AT A LATER DATE.**


1. Read all safety precautions and installation instructions carefully before installing or servicing this fixture. Failure to comply with these instructions could result in potentially fatal electric shock and/or property.
2. It is recommended that all wiring be performed by a qualified electrician. This fixture must be wired in accordance with all national and local electrical codes.
3. Do not handle any energized fixture or attempt to energize any fixture with wet hands or while standing on a wet or damp surface or in water.
4. Make sure that the power source conforms to the requirements of the fixture. (See labels on fixture housing).
5. To reduce the risk of electrical shock, and to assure proper operation, this fixture must be adequately grounded. To accomplish proper grounding, there must be a separate ground wire (green) or bare metal contact (metal conduit) between this fixture and the ground connection of your main power supply panel. The green ground screw location is clearly marked on the fixture housing.
6. This fixture is intended to be used for general indoor lighting in dry or damp locations only.

**NEEDED TOOLS**

- Safety Glasses
- Ruler/Tape Measure
- Flat Blade Screwdriver
- Phillips Screwdriver
- Adjustable Wrench
- Drill
- 3/16" Drill Bit
- 3/32" Drill Bit
- Pliers



Toggle Nut  
4pcs



Screw  
4pcs



Wire Connector  
3pcs

**INSTRUCTIONS**

**TURN OFF POWDER FROM THE MAIN CIRCUIT BEFORE INSTALLING FIXTURE.**

1. To help prevent the possibility of electrical shock, the use for rubber sole shoes is recommended.
2. Carefully remove screw(A), then remove mounting plate(C).
3. Using screw(B) to fix mounting plate(C) on the wall.
4. Electrical Connectors: Connect green/or bare copper wire to the green ground wire of fixture. (Ground wire must be properly attached or unit may not work). Connect the white supply wire to the white fixture wire, cover them with a wire nut/or twist together and cover really well with Electrical tape. Connect the black supplier wire to the black fixture wire, cover them with a wire nut/or twist together and cover really well with Electrical tape.
5. Locate fixture(D) on the mounting plate(C) and using the screw(A) in them to fix.
6. Mount fixture in desired spot. (Make sure the mounting surface is structurally sound).

