



Project	
Notes	
Type	Date
Cat. No.	

BVL™ Series

Curved Bar Vanity Light

DESCRIPTION

The BVL Bathroom Vanity Light brings a graceful, contemporary touch to a range of interior styles. Its round soft white glass shades are complemented by sleek metal components. This fixture is available in a variety of finishes and sizes and can be installed facing up or down.



Specification Features



Construction

White Glass shades surround a curved aluminum bar and mounting plate. Lens design and materials provide uniform appearance without pixelation.

Qualifications

All luminaires are built to UL 1598 and 2108 standards, and bear appropriate ETL labels. Damp location labeling is standard. Emergency equipped fixtures labeled UL924. Adheres to LM70, LM80, and TM21 industry standards. Dedicated 120V Models are FCC Title 47 CFR, Part 15, Class B for residential and commercial applications.

Warranty

3-year limited warranty. See complete warranty for terms and exclusions. (Labor not included).

Electrical

Equipped standard with 120-277V fixed output driver operating at 60 Hz.

Installation

Designed for wall mounting on 4" electrical J-Box.

Rated Life 60,000 hours
Limited Warranty 3 years

Quick Ship

Ordering Information

Example: BVL-3-MB-120D-BN

BVL	2	MB	120D	830	BN
Series BVL Curved Bar Light Vanity	Form Factor 1- 1 Light 2- 2 Light 3- 3 Light 4- 4 Light	Lamp Configuration MB-E26 Medium Socket 8- 8W LED Per Light ²	Driver Type 120D- 120V Triac Dimmable ¹	Color Temp Blank- Blank for MB Configurations 830- 80 CRI, 3000K (For LED Configurations Only)	Finish BL-Black BN-Brushed Nickel

Specifications and Dimensions subject to change without notice

Performance Summary

Input Voltage	120V
Input Frequency	50/60 Hz
Rated Wattage	See Performance Table
Delivered Lumens	See Performance Table
Efficac	90 LPW
CRI	80+, (LED Models)
Available CCT ¹	3000K
Color Consistency ²	5-step MacAdam Ellipse
Rated Life	50,000
L70 ³	> 72,000 hours or > 45,000 >
Power Factor	0.9
THD	< 20%
Dimming	120V Dimming(15-100%)
Operating Temp.	-18°C to 40°C

NOTES:

- ¹ Made to order items. Minimum 90 day lead time. Minimum 500 order quantity.
- ² Energy Star Listed - **Integrated LED Version ONLY**
- ³ Quick ship: 3000K. Other CCTs may require a lead time or be special order
- ⁴ Typical color consistency. May vary or be changed.
- ⁵ L70 hours calculated based on LED package manufacturer LM80 report and ISTMT report of LED in luminaire. Stated values are for select catalog numbers. Contact manufacturer for detailed information



Specifications and Dimensions subject to change without notice

Product Dimensions

Form Factor	1 Light Configuration	2 Light Configuration	3 Light Configuration	4 Light Configuration
Mounting Orientation	Up or Down	Up or Down	Up or Down	Up or Down
Dimensions	Length: 6"	Length: 12-3/4"	Length: 20-1/2"	Length: 27-1/4"
	Height 8-1/2"	Height 8-1/2"	Height 8-1/2"	Height 8-1/2"
	Depth: 5-1/4"	Depth: 5-1/4"	Depth: 5-1/4"	Depth: 5-1/4"