



Project	
Notes	
Type	Date
Cat. No.	

RCH™ Series í GÁÓ^ qā * ÁÓē

Description
 V@ÁRCHÁ^!ā•Áē^Áēē ā Á -Áē qā * Áē • Áēē !ā * Áēē ā] |^Á Á|ēē^Áē • ā } ÉV@Á|Áē Áē ^• Áē ā
 Áēēēē } ēÁē • ā } Á -Áē ÁÓÁ [ē !ÁÓÓÁē Á ē ^• Áē Á |^ ē ēēēēēē } Á Á [^ Áē { ^Áēē !ÉV@Á
 !^ç^! ē|Áēē !^ { ē ^• Áēē Áē Á !-Á &toÁ • ^Áē ^!ā * Áēē !^ Áēē [} ÉÁ



SAT Series
52" Sweep



Limited Warranty 3 years
 Light Source Efficacy: Up to 85 LPW



Special Order

Specification Features

Construction
 Steel Housing, Black Blades and Frosted Glass Light Diffuser provides uniform appearance without pixelation.

Motor
 3-Speed AC Motor with 80" Lead Wire. Includes (1) 5" Downrod.

Blades
 52" Sweep, 5 Blade Configuration Blade
 Pitch Angle: 12°
 Color: Black

Electrical
 Operates at 120V 60HZ. Optional Remote Control (Sold Separately). Optional Wall Control (Sold Separately).

Qualifications
 All ceiling fans are built to UL 507 standards, and bear appropriate ETL labels. Dry location labeling is standard.

Warranty
 Light Source: 3-year limited warranty. Motor: Limited Lifetime Warranty. Non-Electrical 1 Year Limited Warranty. See complete warranty for terms and exclusions. (Labor not included).

Ordering Information

Example: RCH-52-5-3MB-120D-830-BN-PC

RCH	52	5	2MB	120D	830	BN	PC
Series	Size	Fan Blade	Light Source	Driver Type	Color Temp	Finish	Accessory
RCH Ceiling Fan	52- 52" Sweep	5-5 Blades	3MB- 3 Medium Base Socket; (3) 7W 600 Lumen Lamps	120D- 120V Dimming Dims to 10%	830- 3000K; 80+CRI	BN-Brushed Nickel WH- White BL- Black	PC- Pull Chain

Specifications and Dimensions subject to change without notice.

Lighting Performance Summary

Input Voltage	120V
Input Frequency	50/60 Hz
Rated Wattage	See Performance Table
Delivered Lumens	See Performance Table
Efficacy	> 89 LPW (typ.)
CRI	80+, R9> 0
Available CCT ¹	3000K
Color Consistency ²	5-step MacAdam Ellipse
Rated Life	50,000 hours
L70 ³	> 72,000 hours or > 45,000
Power Factor	>0.99
THD	< 20%
Dimming	Triac Dimming
Operating Temp.	-18°C to 40°C

Fan Performance Summary

Fan Diameter	52"
Motor Lead Lengths	80"
Motor Size	AC 153mm x 13mm
Electricity Use (H/M/L)	73.98W/34.5W/12.56W
AMPS (H/M/L)	0.49/0.35/0.21


Lighting Performance Data

Lens Type	Form Factor	Catalog No.	Rated Wattage (W)	Delivered Lumens	Efficacy (lm/W)
Frosted Glass	52"	RCH-52-5-3MB-120D-930	21W	1800	85

Fan Performance Data

RPM (H/M/L)	172/121/69
Airflow Efficiency (CFM/W)	93
Airflow (CFM)	High Speed: 4,784
Average Airflow CFMav	3,404

Product Dimensions



NOTES:

- Made to order items. Minimum 90 day lead time. Minimum 500 order quantity.
- Energy Star Listed **N/A**
- Typical color consistency. May vary or be changed.
- L70 hours calculated based on LED package manufacturer LM80 report and ISTMT report of LED in luminaire. Stated values are for select catalog numbers. Contact manufacturer for detailed information
- Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C.



Specifications and Dimensions subject to change without notice.