

LED Glass T8 Hybrid Tubes LHT8 Series





Ordering Information



LHT8 Series

(10W, 1400 Lumens, 24") (12W, 1900 Lumens, 48") (15W, 2200 Lumens, 48")







Specification Features

Qualifications

All luminaires are built to UL 1598 and 2108 standards, and bear appropriate ETL labels. Damp location labeling is standard. Emergency equipped fixtures labeled UL924. Adheres to LM70, LM80, and TM21 industry standards. DesignLights Consortium® (DLC) DLC qualified product. Not all models of this product may be DLC qualified. Please check the DLC Qualified Products List at www.designlights.org/QPL to confirm which models are qualified.

Warranty

5-year limited warranty. See complete warranty for terms and exclusions. (Labor not included).

Construction

Full glass construction with inner phosphor coating and aluminum end caps. Nearly identical look to a fluorescent lamp. 240° light distribution.

Installation

Dual mode internal driver automatically adapts to fluorescent ballasted fixtures or direct AC voltage formats, 120-277V. May be used with shunted/ non-shunted sockets on direct AC voltage.

Rated Life 50,000 hours Limited Warranty 5 years Efficacy up to 158 LPW

Quick Ship

LHT8-10-835-FC
LHT8-10-840-FC
LHT8-10-850-FC
LHT8-12-835-FC
LHT8-12-840-FC
LHT8-15-835-FC
LHT8-15-835-FC
LHT8-15-840-FC
LHT8-15-850-FC

Ordering Information

Example: LHT8-15-840-FC

LHT8	15	8	50	FC	
Series LHT8 LED Glass T8 Hybrid Tubes	Rated Wattage 10-(10W,1400 Lumens, 24") ^{1 2} 12-(12W,1900 Lumens, 48") ^{1 2} 15-(15W,2200 Lumens, 48") ²	8 80+ CRI ²	35 3500 K ² 40 4000 K ² 50 5000 K ²	Lens FC- Frosted Coating ²	

Specifications and Dimensions subject to change without notice.

- Made to order items. Minimum 90 day lead time. Minimum 500 order quantity.
- 2 DLC Listed