
Ordering Information

Dimensions



Specification Features

Construction

Contemporary styled fixture. Two twin steel rings surrounded a high-transmission frosted plastic diffuser designed to eliminate glare and optimize lumen output.

Qualifications

All luminaires are built to UL 1598 and 2108 standards, and bear appropriate ETL labels. Damp location labeling is standard. Emergency equipped fixtures labeled UL924. Adheres to LM70, LM80, and TM21 industry standards. ENERGY STAR® certified product (for 3000K and 4000K only) and Title 24 qualified. Dedicated 120V Models are FCC Title 47 CFR, Part 15, Class B for residential and commercial applications. California Title 24 Compliant, JA8 compliant, CEC Listed.


Warranty

3-year Limited Warranty. See warranty documentation for more information.

Ordering Information

Example: OWS-	9-120-930-GY				
ows	9	120	9	30	GY
Series	Rated Wattage	Driver Type	CRI	Color Temp	Finish
OWS Outdoor Wall Sconce	9 -9W,(800 Lumens) ²	120- 120V ²	9 90+CRI	30 -3000 K ²	GY- Grey BR- Bronze

Specifications and Dimensions subject to change without notice.





Electrical Equipped standard with 120V-277V driver.

Installation

Designed for wall mounting on 4" electrical J-Box.

Quick Ship

OWS Series

9W(800 Lumens)

Rated Life 50,000 hours

Efficacy Up to 88 LPW

Limited Warranty 3 years

OWS-9-120-930-GY